



# Installing The WV-S Dragon Wall Vent.

- 1:** Locate where the WV-S wall vent is to be installed, there will need to be a penetration made in the brick work to the dimensions of 200mm x width and 185mm x Hight.
- 2:** Place the WV-S wall vent in the area made as per instructions. Place a level on top of the vent, when the vent is level mark all four holes.
- 3:** With a 5.5mm masonry drill bit start to drill the four holes marked, insert wall plugs supplied in kit.
- 4:** Attach flexy duct to the vent with cable ties supplied, feed flexy duct through the wall to connect to the appliance.
- 5:** Insert the vent back on the wall, start fasten vent with screws supplied making sure the vent is secured level.
- 6:** Insert the stainless steel mesh on the wall vent ,line up with the designated holes.
- 7:** Secure the stainless mesh with screws supplied.
- 8:** We recommend a bead of clear water proof silicone applied on the top of the vent between the vent and the wall, this can be clean over with a damp cloth.

## Installation Tips:

- Make sure the penetration is the correct size at least 200mm wide and 185 mm high.
- Make sure duct is pulled taught without tearing so there is no excess flexi duct.
- Do not exceed measurements this may effect the fixing of the vent to the wall.

- Tools required for installation.



***For more info on installing the WV-D wall vent please visit our website at***

**[www.homeventingsolutions.com.au](http://www.homeventingsolutions.com.au)**

1



2



3



4



5



6



7



8





# Installing The WV-D Dragon Wall Vent.

- 1:** Locate where the WV-D wall vent is to be installed, there will need to be a penetration made in the brick work to the dimensions of 320mm x width and 165mm x Hight.
- 2:** Place the WV-D wall vent in the area made as per instructions. Place a level on top of the vent, when the vent is level mark all four holes.
- 3:** With a 5.5mm masonry drill bit start to drill the four holes marked, insert wall plugs supplied in kit.
- 4:** Attach flexy duct to the vent, feed flexy duct through the wall to connect to the appliance.
- 5:** Insert the vent back on the wall, start fasten vent with screws supplied making sure the vent is secured level.
- 6:** Insert the stainless steel mesh on the wall vent ,line up with the designated holes.
- 7:** Secure the stainless mesh with screws supplied.
- 8:** We recommend a bead of clear water proof silicone applied on the top of the vent between the vent and the wall, this can be clean over with a damp cloth.

## Installation Tips:

- Make sure the penetration is the correct size at least 320mm wide and 165 mm high.
- Make sure duct is pulled taught without tearing so there is no excess flexi duct.
- Tools required for installation.



***For more info on installing the WV-D wall vent please visit our website at***

**[www.homeventingsolutions.com.au](http://www.homeventingsolutions.com.au)**



# Installing The WV-D Dragon Wall Vent.

1.



2.



3.



4.



5.



6.



7.



8.

